

Interstella Difussed Series LED Downlight



7W Compact

7W

12W



15W

18W

Features

- High grade aluminium construction with excellent heat diffusion properties
- High quality SMD LED chipset with efficiency up to 80Lm/W
- UV stabilised cover with excellent light penetration, soft and even light distribution
- Environmentally friendly, free from mercury content
- Does not emit harmful infrared or UV rays
- Flicker Free and high CRI for truer colours
- Long lifespan for lower maintenance costs
- Built-in LED driver, PF≥0.95
- Warm White, Cool White or Daylight Colour temperature options
- 3 Years manufacturer's warranty

Applications: Residential, Nursing Home, Education, etc

Specifications

Order no.	Wattage	CCT	Model.	Cut-out(mm)	Lm	Voltage
PAK-U06-001-7W03-840-W	7W	4000K	3 inch	φ100	480	AC100-240
PAK-U06-001-7W03-860-W	7W	6000K	3 inch	φ100	550	AC100-240
PAK-U06-001-7W04-840-W	7W	4000K	4 inch	φ110	470	AC100-240
PAK-U06-001-7W04-860-W	7W	6000K	4 inch	φ110	550	AC100-240
PAK-U06-001-12W05-840-W	12W	4000K	5 inch	φ135	870	AC100-240
PAK-U06-001-12W05-860-W	12W	6000K	5 inch	φ135	950	AC100-240
PAK-U06-001-15W06-840-W	15W	4000K	6 inch	φ165	1100	AC100-240
PAK-U06-001-15W06-860-W	15W	6000K	6 inch	φ165	1250	AC100-240
PAK-U06-001-18W08-840-W	18W	4000K	8 inch	φ210	1300	AC100-240
PAK-U06-001-18W08-860-W	18W	6000K	8 inch	φ210	1650	AC100-240

[^]For warm white colours, replace last 3 digits with 30-W (instead of 40-W or 60-W)