

Features

- COB Downlight with great energy saving and high luminous efficacy
- Die-cast aluminium alloy construction with powder coated finish
- High purity aluminium reflector maximizes reflectivity and use of light
- Embedded LED chipset design for better glare control
- High efficiency constant current LED driver
- Ideal for general lighting in large spaces

Product Image



Specifications

Model No.	Part No.	Power	Lumens	CCT	Voltage	Beam Angle	Cutout (mm)	Pack QTY
PAK560198	PAK-LED-C102-10W3A-30-W	10W	800lm	3000K	220V/50Hz	120°	Ø95	12
PAK560198	PAK-LED-C102-10W3A-40-W	10W	800lm	4000K	220V/50Hz	120°	Ø95	12
PAK560280	PAK-LED-C102-20W4A-30-W	20W	1300lm	3000K	220V/50Hz	120°	Ø130	12
PAK560280	PAK-LED-C102-20W4A-40-W	20W	1300lm	4000K	220V/50Hz	120°	Ø130	12
PAK560300	PAK-LED-C102-30W5A-30-W	30W	2330lm	3000K	220V/50Hz	120°	Ø150	12
PAK560300	PAK-LED-C102-30W5A-40-W	30W	2330lm	4000K	220V/50Hz	120°	Ø150	12
PAK560290	PAK-LED-C102-40W6A-30-W	40W	2500lm	3000K	220V/50Hz	120°	Ø170	12
PAK560290	PAK-LED-C102-40W6A-40-W	40W	2500lm	4000K	220V/50Hz	120°	Ø170	12