

# Item: LED Display Spotlight

## Features

- Quality SMD chips, high luminous efficiency, with excellent color consistency and high CRI.
- High grade aluminium alloy construction with powder coated finish
- Integrated lens design with even light distribution
- High quality thermal conductive aluminium heat sink, effectively dissipates heat from led chips
- Dedicated constant current led driver ensures reliable performance
- Lifespan is up to 30000 hours

## Product Image & Fixture Diagram



## Specifications

Model No.	Part No.	Power	CCT	Lumens	Beam Angle	Fixture Size (mm)	Voltage
PAK564130	PAK-LED-S605-3WB1-30-W	3W	3000K	220	24°	92x92x48	240V
PAK564130	PAK-LED-S605-3WB1-40-W	3W	4000K	220	24°	92x92x48	240V
PAK564110	PAK-LED-S605-6WB1-30-W	6W	3000K	420	24°	92x92x48	240V
PAK564110	PAK-LED-S605-6WB1-40-W	6W	4000K	420	24°	92x92x48	240V
PAK564120	PAK-LED-S605-6WB2-30-W	2x6W	3000K	840	24°	92x175x48	240V
PAK564120	PAK-LED-S605-6WB2-40-W	2x6W	4000K	840	24°	92x175x48	240V